GAS-DETECTORS

300 HC & CO

For combustible gases or for carbon monoxide
— with integrated power supply —

Gas detector 300 HC

for combustible gases

Perfectly suitable to locate gas leakages in the installation area. With means of the flexible sensor neck, the sensor can be introduced to areas difficult of access.

More advantages, of the easy handling are the compact case, the integrated power supply and the well legible display indication.

The programmable alarm tresholds will be indicated via sonic signal and flashing display.

Measuring data can be saved in the internal data memory or printed via the integrated IR interface.

TECHNICAL DATA:

Indication:	in ppm, % or LEL in the well legible display
Data storage:	20 measurements max. value and average value
Measuring range:	0 – 20.000 ppm
Alarm:	acoustic signal and flashing display
Alarm treshold:	programmable
Power supply:	2 x batteries, LR6 AA
Operation time:	approx. 8 hours continuous operation
Dimensions: W x H x D	case 84 x 139 x 24 mm sensor neck lenght 330 mm
Weight:	approx. 230 g
Order No.:	680500

Gas detector 300 CO

for carbon monoxide (ambient air)
(other toxic gases on request)

Reliably and quickly detects toxic carbon monoxide in the ambient air.

The alarm treshold is programmable within the measuring range of 0–300 ppm.

Handling, alarm signal, measuring value indication, data memory, average value calculation and print function see 300 HC.

TECHNICAL DATA:

Indication:	in ppm in the well legible display
Data storage:	20 measurements max. value and average value
Measuring range:	0 – 300 ppm
Alarm:	acoustic signal and flashing display
Alarming barrier:	programmable
Power supply:	2 x batteries, LR6 AA
Operation time:	approx. 1000 hours continuous operation
Dimensions: W x H x D	case 84 x 139 x 24 mm
Weight:	approx. 230 g
Order No.:	680400

WA BRUDER · B-58238-K0-10-091-HWH